Product data sheet

FLEXBAR SURFACE / SUSPENDED - 39W (14W/M) - PRIMARY STRAIGHT - 2800MM - UP & DOWNLIGHT - BLACK REF - 40…
EFR39LPUB


THORLUX LIGHTING



IP 20

Flexbar is an elegant surface mounted or suspended linear luminaire ideal for a wide range of applications. The high performance lens technology provides well-controlled low glare lighting for optimum user comfort. Individual and continuous versions along with corner joints allow the lighting designer to be creative with their lighting layouts. Supreme efficiency (160.5 LL/cW) and 100,000 hour life ensures Flexbar has the performance to match its beauty. Applications: Offices, teaching spaces, meeting rooms, breakout areas, reception areas, circulation spaces and retail


Light output 1 (emergency)



1 x LED

Nominal lamp power	39 W	LOR	100%
Lamp flux	5720 lm	Total flux	5720 lm
Luminous efficacy	124 lm/W	Total power	46 W
CCT	4000 K		
CRI	80		

Light output 2



1 x LED

Nominal lamp power	39 W	LOR	100%
Lamp flux	5720 lm	ULOR	20%
Luminous efficacy	124 lm/W	Total flux	5720 lm
CCT	4000 K	Total power	46 W
CRI	80		

Mounting mode

Pendant, Ceiling mounted

Shape and measurements

Length: 110.24 in
Width: 1.73 in
Height: 2.40 in

Adjustability

Fixed, Height adjustable

Electric

System power: 92 W

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Protection

IP: 20