
Product data sheet

CEILING MOUNTED LUMINAIRE SOLO SLIM OFFICE L2 25W 3450LM CRI > 80 3000K BLACK DALI 530MM
2011.3645 - SOLO SO CM530 LED3450-830 DID BK DALI


REGENT



IP 40 IK 07

Ceiling mounted luminaire Solo Slim Office with LED, system power: 25 W, luminous flux of luminaire 3450 lm, standby power 0.5 W, colour rendering index CRI > 80, 3000 K, warm white, colour tolerances SDCM 3, lifetime LED L80 50'000 h, office-compatible and glare-free according to EN 12464-1 (UGR < 19; Lmax ≥ 65° ≤ 3000 cd/m²), photobiological safety: the luminaire poses no danger (RG0), 230 V, direct-indirect light emission, frame in aluminium nominal current: 0.108 A, black, neat shadow gap, diffuser in polymethyl methacrylate (PMMA) office-suitable microprismatic CLD optics (Controlled Luminance Diffusor) for perfect glare control, 1 integral control gear, DALI, ENEC certified, Certified Regent MINERGIE® module luminaires S.A.F.E. 2019 (Re-0282), luminaire meets the strict requirements for Minergie luminaires protection class I, ingress protection IP40, glow wire test 650 °C, impact strength: IK 07, this product contains a light source of energy efficiency class B and EPREL registration number: 1712293 Ø = 530 mm, H = 81 mm

Light output 1



1 x LED

Nominal lamp power	31 W	LOR	100%
Lamp flux	3450 lm	Total flux	3449 lm
Luminous efficacy	111 lm/W	Total power	25 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 20.87 in
Width: 20.87 in
Height: 3.23 in
Weight: 26.453 kg

Adjustability

Fixed

Design

Color of housing: Black

Electric

System power: 25 W
Appliance Class: I

Protection

IP: 40
IK: 07