


Product data sheet

TENTEC ACCENT RECESSED LUMINAIRE, SAFETY SCREEN
TL2102501-30-30 + 83817Q08-60_23W
SCHMITZ | WILA



Tentec accent LED 3000 K Recessed Luminaire, Light distribution direct Downlight with lite optic Safety Screen Product: TL2102501-30-30
Operating technology: independent driver required Lite Optic: 83817Q08-60 Lite Optic Safety Screen Tempered safety glass Aluminium reflector (Al99.98), high-polished Half-peak divergence $\alpha = 60^\circ$ Light Technique CRI > 80 High chromaticity stability with 3SDCM (initial) Constant colour temperature 3000 K Lifetime 50.000 h (L70) Luminaire housing stable housing design, made of aluminium die-cast and UV resistant plastics minimised frame thickness of only 2 mm for homogeneous appearance in the ceiling frame colour white, RAL 9016
Operating and assembly technology LED driver to be ordered separately Driver suitable for connection to central battery systems Quick installation due to 2-point screw fixing Suitable for ceiling thicknesses of 12-25 mm (1-12 mm by using optional extension kit, Art.-No. 89081) Reflector with safety suspension Lamp Wattage: 23 W Colour Rendering Index: 80 Colour Temperature: 3000 K Luminaire Luminous Flux: 1950 Lm System Efficiency: 75 Lm/W Half-peak Divergence α : 60° Number Luminaires LZ: 0.06 Connector: screw connector, 2 x 1.5 mm² Reflector Size: Q08 Length: 102 mm Width: 102 mm Cut-out length: 95 mm Cut-out width: 95 mm Installation Depth RD: 110 mm Total Weight: 0.6 kg Degree of Protection IP44, IP44 in closed ceiling systems CE-Sign Total system: Protection class 2 Data record TL2102501-30-30+83817Q08-60_23W

Light output 1



1 x General service incandescent lamp

| | | | |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 26 W | LOR | 100% |
| Lamp flux | 1950 lm | Total flux | 1950 lm |
| Luminous efficacy | 75 lm/W | Total power | 26 W |
| CCT | 3000 K | | |
| CRI | 80 | | |

Mounting mode

Ceiling recessed

Shape and measurements

Length: 4.02 in
Width: 4.02 in
Height: 4.33 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 26 W
Appliance Class: II

Protection

IP: 44