Product data sheet

HALO SUSPENSION DI/ID BLACK 1360MM
R48H136-9005E2930H3S
PLANLICHT



IP 40 CE

LED HCL 2700-6500K CRI>90 85,9W 6430lm DALI https://katalog.planlicht.com/en-gb/fam-halo/

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	17.75 W	CRI	90
Total flux	1266 lm	LOR	100%
Luminous efficacy	71 lm/W	Total power	17.75 W

Light output 2 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	17.75 W	CRI	90
Total flux	1266 lm	LOR	100%
Luminous efficacy	71 lm/W	Total power	17.75 W

Light output 3 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	17.75 W	CRI	90
Total flux	1266 lm	LOR	100%
Luminous efficacy	71 lm/W	Total power	17.75 W

Light output 4 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	17.75 W	CRI	90
Total flux	1266 lm	LOR	100%
Luminous efficacy	71 lm/W	Total power	17.75 W

Light output 5 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	17.75 W	CRI	90
Total flux	1266 lm	LOR	100%
Luminous efficacy	71 lm/W	Total power	17.75 W

Light output 6 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	17.75 W	CRI	90
Total flux	1266 lm	LOR	100%
Luminous efficacy	71 lm/W	Total power	17.75 W

Light output 7 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	17.75 W	CRI	90
Total flux	1266 lm	LOR	100%
Luminous efficacy	71 lm/W	Total power	17.75 W

Light output 8 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	17.75 W	CRI	90
Total flux	1266 lm	LOR	100%
Luminous efficacy	71 lm/W	Total power	17.75 W

Mounting mode

Pendant

Shape and measurements

Length: 53.54 in
Width: 53.54 in
Height: 2.44 in

Adjustability

Fixed

Electric

System power: 142 W

Protection

IP: 40
Designation labels: CE