


Product data sheet

SLOIN SLIM SL LED6000-830 LDE L4004 PCO
42183945
ZUMTOBEL



DALI-dimmable LED light line with LED converter; LED service life lasts 50000 h before luminous flux is reduced to 85% of the initial value. Chromaticity tolerance (initial MacAdam): 3. Luminaire luminous flux: 5910 lm, Luminaire efficacy: 61 lm/W. Colour rendering Ra > 80, colour temperature 3000 K. Luminaire of aluminium, silver powder coated. Luminaire with completely uniform appearance due to polycarbonate cover. Light distribution with UGR < 22 in accordance with EN 12464-2011. Luminaire consists of housing and continuous optic of polycarbonate. Includes gear tray, wiring, and end-cap set. Luminaire wired with halogen-free leads and covers are due to norm classified as TP(a). Degree of protection: IP20. Dimensions: 4004 x 45 x 64 mm weight: 10.4 kg

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	97.4 W	CRI	80
Total flux	5910 lm	LOR	100%
Luminous efficacy	61 lm/W	Total power	97.4 W

Mounting mode

Pendant

Shape and measurements

Length: 157.64 in
Width: 1.77 in
Height: 2.52 in
Weight: 10.4 kg

Design

Material impression: Aluminum
Color of housing: Silver gray

Electric

System power: 97.4 W
Voltage: 220-240 V AC
Controller: DALI
Appliance Class: I

Protection

IP: 20
Designation labels: CE, ENEC