

Product data sheet


VOLICA 2.0 LED SYSTEM DALI 2400 7050LM 4000K OPAL MATT (PMMA) WHITE
010501.3L08.114

LUG



Decorative system luminaire for LED light sources; aluminum profile available in various colors, equipped with an efficient lighting system, optimized for indoor use. The luminaire is available in surface-mounted or suspended version, depending on the purchased accessories. Mounting: suspended, on wire suspension (on request), surface mounted Body: aluminum profile Power supply efficiency: >87% Power: 220-240V 50/60Hz Includes light source: yes Lifetime (L80B10): 100 000 h Lifetime (L90B10): 50 000 h Warranty: 5 years Application: offices, hotels, reception desks, galleries, auditorium, boutiques, museums

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	56 W	CRI	80
Total flux	7050 lm	LOR	100%
Luminous efficacy	126 lm/W	Total power	56 W

Mounting mode

Pendant, Ceiling mounted

Shape and measurements

Length: 94.49 in

Width: 2.36 in

Height: 3.15 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 56 W

Controller: DALI

Appliance Class: I

Protection

IP: 20

IK: 04