
Product data sheet


LINEDO_4,5M_OH_11111111
9545OH.830.476.000
RZB



IP 54 IK 04


LINEDO, 81 W, 11400 lm, 830, aluminium, DALI Continuous line luminaire, L 4547 B 58 H 91

Light output 1 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	10.13 W	CRI	80
Total flux	1425 lm	LOR	100%
Luminous efficacy	141 lm/W	Total power	10.13 W

Light output 2 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	10.13 W	CRI	80
Total flux	1425 lm	LOR	100%
Luminous efficacy	141 lm/W	Total power	10.13 W

Light output 3 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	10.13 W	CRI	80
Total flux	1425 lm	LOR	100%
Luminous efficacy	141 lm/W	Total power	10.13 W

Light output 4 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	10.13 W	CRI	80
Total flux	1425 lm	LOR	100%
Luminous efficacy	141 lm/W	Total power	10.13 W

Light output 5 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	10.13 W	CRI	80
Total flux	1425 lm	LOR	100%
Luminous efficacy	141 lm/W	Total power	10.13 W

Light output 6 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	10.13 W	CRI	80
Total flux	1425 lm	LOR	100%
Luminous efficacy	141 lm/W	Total power	10.13 W

Light output 7 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	10.13 W	CRI	80
Total flux	1425 lm	LOR	100%
Luminous efficacy	141 lm/W	Total power	10.13 W

Light output 8 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	10.13 W	CRI	80
Total flux	1425 lm	LOR	100%
Luminous efficacy	141 lm/W	Total power	10.13 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 2.28 in
Width: 179.02 in
Height: 3.58 in

Adjustability

Fixed

Electric

System power: 81.04 W

Protection

IP: 54
IK: 04