



# Product data sheet

GUIDELED SL 13812 1-8H/D CGLINE+ (SET TO 8 H OPERATION)  
40071353279  
EATON EMERGENCY LIGHTING



• LED self contained luminaire with automatic test for reduced inspection effort • Universal use for maintained and non-maintained operation and for 1 h, 3 h or 8 h operation • For autonomous installation or connection to the CGLine monitoring system • Environmentally-friendly due to modern lithium ion technology • Low operating costs via low connected load • Minimum maintenance effort via high LED service life (50,000 hours) • Available with special optics for escape route illumination or open-area illumination • High spacing via double optics technology and highly efficient High Power LEDs • Simple fault analysis and status display via bicolor LED and testing button • 1 minute switch-back delay after mains return (according to DIN VDE 0100-718) • Blocking function prevents unintended discharge during idle operating times (only with CG controller or CGLine WEB-Interface)

## Light output 1 (integrated, emergency)



Lamp type	LED	CCT	6500 K
Nominal lamp power	6.7 W	CRI	70
Total flux	105 lm	LOR	100%
Luminous efficacy	16 lm/W	Total power	6.7 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 6.77 in  
Width: 6.77 in  
Height: 1.57 in

## Adjustability

Fixed

## Design

Color of housing: White

## Electric

System power: 6.7 W  
Appliance Class: I

## Information regarding emergency functions

Emergency lighting only  
Emergency power supply: Single battery 1 h, Single battery 3 h, Single battery 8 h  
Emergency sign: N/A

## Protection

IP: 41  
IK: 03  
Designation labels: CE