



Product data sheet

MIDDLE EAST TA 55 1.5FT PCC 5500/840 1F
51561
TREVOS



design optimised for rooms with ambient temperatures up to 55 °C; optimal mounting height: 3.5 to 10 m; ON/OFF electronic driver (AC, DC on demand); Body: grey PC (high mechanical resistance, UV stability, RAL 7035); Diffuser: translucent PC (high mechanical resistance, UV stability); Reflector: steel sheet, white (RAL 9003); Clips: stainless steel + polyamide; Sealing: polyurethane (PUR), foam-filled base groove; Connection: screwless three-pole terminal block, 3-wire connecting cabling for feed-through installation (1.5 mm² cross-section, 2.5 mm² available on demand); Power: 38,3 W; Luminaire flux: 5400 lm; Lifetime: L90/B10; 50000 hours; Impact strength: IK10; Ambient temperature: -25|55 °C; Weight: 2,3 kg;

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	38.3 W	CRI	80
Total flux	5740 lm	LOR	100%
Luminous efficacy	150 lm/W	ULOR	4%
		Total power	38.3 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 57.17 in

Width: 5.71 in

Height: 4.41 in

Adjustability

Fixed

Design

Material impression: Plastic

Color of housing: Silver gray, White

Designer: TREVOS

Electric

System power: 38.3 W

Ballast: ECG

Appliance Class: I

Protection

IP: 44

IK: 10

Designation labels: CE

Other operating numbers

Ambient temperature range: -13...131°F