


Product data sheet

APOLLO G2 INDUSTRY 1560MM PM 2X38W 030° 12000LM
9480295D
PRACHT



New generation of the proven APOLLO damp-proof reflector luminaire in the industry version. Redesigned beautiful frame-end-pieces made of PBT. Simple one-man assembly of the reflector with integrated plug and directional guide and captive, easy-to-close clips made of stainless steel. Seamless enclosed tubular housing made of white, fibre-glass reinforced, hardly inflammable, largely acid and alkali-resistant polyester resin. Protection class IP65. Reflector with integrated industry LED circuit boards can be swiveled through 120 °, with practical detent mechanism in 10 ° steps. Short, ageing-resistant silicone seals. Durable industrial grade electronic ballast integrated. Particularly robust due to thermal decoupling of LED and converter. Through-wiring up to max. 5x2.5mm² + 2x1.5mm² possible. The permissible ambient temperature decreases by 1°C per 2A of the through-wiring. Variable mounting points with PRACHT CLAMP SYSTEM made of stainless steel, suitable for ceiling and horizontal wall mounting, accessories for pendant and mounting rail installation available for order.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	76 W	CRI	80
Total flux	12000 lm	LOR	100%
Luminous efficacy	158 lm/W	ULOR	2%
		Total power	76 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 61.42 in
Width: 9.13 in
Height: 5.59 in
Weight: 4.7 kg

Adjustability

Tiltable

Electric

System power: 76 W
Appliance Class: I

Protection

IP: 65
IK: 06

Other operating numbers

Ambient temperature range: -49...140°F