Product data sheet

SIDELITE SQUARE
311636.004.1.76
RZB



IP 40 IK 03

Series: Sidelite Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 0 Hz, 50 - 60 Hz Fitting sheet steel powder-coated, frame aluminium anodised, diffuser plastic, prismatic on one side. Steel cable suspension infinitely adjustable to 3000mm, with conical canopies. Converter integrated. Sidewards light input with LED, lamps (LED) included in delivery. Available Colours: anodised aluminium Type of Installation: Pendant Dimensions: L 1198, B 298, H 46 Lamp: LED Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Converter, dimmable, DALI Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 4150lm System power: 48W Beam Angle: 96° Number of fittings B10A: 10 Number of fittings B16A: 16 Number of fittings C10A: 16 Number of fittings C16A: 26 Inrush current: 26A Unified Glare Ratio: 18,3 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	48 W	CRI	80
Total flux	4150 lm	LOR	100%
Luminous efficacy	86 lm/W	Total power	48 W

Mounting mode

Pendant

Shape and measurements

Length: 11.73 in
Width: 47.17 in
Height: 0.79 in

Adjustability

Fixed

Electric

System power: 48 W

Protection

IP: 40
IK: 03