Product data sheet

POLE MOUNTED LUMINAIRE RESIDENZA-2 ZERO CIR06 16LED 2700K
88.00900.0VXXX
HESS



IP 65

Protective cover made of PC glass. Luminaire rests on four aluminium rods. Cylindrical luminaire body made of cast aluminium, universal holder for poles with spigot 60.3 - 82.5 mm. Luminaire enclosure made of PC, clear. Diameter 200mm. ULOR of 0%, complies with the Dark Sky Standard. Rods and internal parts uniformly painted, dark anthracite textured (similar to DB 703/Gris 2900 sablé)

Light output 1



1 x LED

Nominal lamp power	29.4 W	LOR	100%
Lamp flux	3729 lm	Total flux	3729 lm
Luminous efficacy	127 lm/W	Total power	29.4 W
CCT	2700 K		
CRI	80		



1 x LED

Nominal lamp power	27.1 W	LOR	100%
Lamp flux	3439 lm	Total flux	3439 lm
Luminous efficacy	127 lm/W	Total power	27.1 W
CCT	2700 K		
CRI	80		



1 x LED

Nominal lamp power	24.8 W	LOR	100%
Lamp flux	3144 lm	Total flux	3144 lm
Luminous efficacy	127 lm/W	Total power	24.8 W
CCT	2700 K		
CRI	80		



1 x LED

Nominal lamp power	22.5 W	LOR	100%
Lamp flux	2842 lm	Total flux	2842 lm
Luminous efficacy	126 lm/W	Total power	22.5 W
CCT	2700 K		
CRI	80		



1 x LED

Nominal lamp power	20.2 W	LOR	100%
Lamp flux	2537 lm	Total flux	2537 lm
Luminous efficacy	126 lm/W	Total power	20.2 W
CCT	2700 K		
CRI	80		



1 x LED

Nominal lamp power	18 W	LOR	100%
Lamp flux	2223 lm	Total flux	2223 lm
Luminous efficacy	124 lm/W	Total power	18 W
CCT	2700 K		
CRI	80		



1 x LED

Nominal lamp power	15.7 W	LOR	100%
Lamp flux	1899 lm	Total flux	1899 lm
Luminous efficacy	121 lm/W	Total power	15.7 W
CCT	2700 K		
CRI	80		



1 x LED

Nominal lamp power	13.4 W	LOR	100%
Lamp flux	1569 lm	Total flux	1569 lm
Luminous efficacy	117 lm/W	Total power	13.4 W
CCT	2700 K		
CRI	80		



1 x LED

Nominal lamp power	11.1 W	LOR	100%
Lamp flux	1226 lm	Total flux	1226 lm
Luminous efficacy	110 lm/W	Total power	11.1 W
CCT	2700 K		
CRI	80		



1 x LED

Nominal lamp power	33.9 W	LOR	100%
Lamp flux	4291 lm	Total flux	4291 lm
Luminous efficacy	127 lm/W	Total power	33.9 W
CCT	2700 K		
CRI	80		



1 x LED

Nominal lamp power	31.6 W	LOR	100%
Lamp flux	4012 lm	Total flux	4012 lm
Luminous efficacy	127 lm/W	Total power	31.6 W
CCT	2700 K		
CRI	80		

Mounting mode

Pole top mounted

Shape and measurements

Length: 8.03 in
Width: 8.03 in
Height: 26.41 in

Adjustability

Fixed

Electric

System power: 11.1-33.9 W

Protection

IP: 65