Product data sheet

ILDL428SC-SW - RUND
ILDL428SC-SW
RP-TECHNIK

IP 40 IK 03

The IL LED safety light with its unobtrusive design is a real all-rounder. Whether as a self-contained light or for connection to central battery systems: it is equipped for almost all requirements and always offers the right solution. The innovative integrated lens carrier with quick-mounting device enables the flexible use of different lens types depending on the application. Round and corridor lenses are already included in the scope of delivery for each light and enable perfect adaptation to the respective installation situation. All versions of the IL are available for surface and recessed mounting. The IL surface-mounted light consists of only 2 parts, with the ceiling attachment containing the mains connection terminals. The actual lamp is installed without tools and is not connected to the mains voltage when it is dismantled. Housing color black RAL 9005

Light output 1 (emergency)



1 x LED

Nominal lamp power	1.9 W	LOR	89%
Lamp flux	125 lm	Total flux	111 lm
Luminous efficacy	66 lm/W	Total power	3 W
CCT	6500 K		
CRI	70		

Mounting mode

Ceiling mounted

Shape and measurements

Height: 1.42 in
Diameter: 3.94 in

Adjustability

Fixed

Design

Color of housing: Black

Electric

System power: 3 W
Appliance Class: I

Information regarding emergency functions

Emergency lighting only
Emergency sign: N/A

Protection

IP: 40
IK: 03
Designation labels: CE

Other operating numbers

Ambient temperature range: 23...104°F