

Product data sheet


RING 2 LED D4I 12 B 4000K VS
2121527/B/4/VS/10KV
ROSA



IP
66

A luminaires from the RING LED series, with a rounded cap made of formed aluminum sheet and a diffuser made of tempered glass. The luminaire body is made of aluminum. It can be used, among others, around office buildings, in parks, along communication routes and in parking lots. It has a ingress protection level of IP 66. Depending on the head type, the luminaire is mounted: A - directly on a pole or arm with a $\varnothing$ 60 x 50 mm ending; B - directly on the pole with an end $\varnothing$ 60 x 180 mm. Equipped with PMMA lenses and replaceable LED module. The operating temperature range is from -40°C to +40°C. The expected service life of the product is L90B10 - 100,000 h. Supply voltage frequency 50/60Hz. Power factor ≥ 0.95 . The luminaire can be connected to an external control system via the DALI interface (optional support for an analog 1-10V signal).

Light output 1



1 x LED			
Nominal lamp power	15 W	LOR	82%
Lamp flux	2700 lm	Total flux	2214 lm
Luminous efficacy	180 lm/W	Total power	15 W
CCT	4000 K		
CRI	70		

Mounting mode

Pole top mounted

Electric

System power: 15 W

Shape and measurements

Height: 8.74 in
Diameter: 22.83 in

Protection

IP: 66

Adjustability

Fixed