Product data sheet


MICRO KUBIK - CV GROUND MOUNT
5948-H-2-562-XX
UNILAMP



IP 66 IK 06

Description KUBIK is a robust cube-shaped spotlight with LED light source. The family offers ground/wall mount fixing, pole clamp and wall clamp setting, indirect pole light and wall light. The front glass cover flushes to the surface and there is no accumulation of dust and water. High efficiency reflectors and lens are used in this luminaire family. Aiming can be done through graduated scale by tool. A special designed body housing separates lamp compartment from the control gear. KUBIK is suitable to light up object from short to medium distance like brushes, plants, sculptures, flags, signboards, columns, building facets, etc. spec • Designed, Manufactured and Tested according to IEC 60598-1, IEC 60598-2-1 and VDE regulations. • LM6 Die Cast Aluminium and Extruded Aluminium body. • Stainless steel screws. • Nano Ceramic surface conversion. • Double layer coating. • Safety glass cover. • Post-cured silicone gasket. • High quality LED module and driver. • High efficiency reflector. • Molded lens from renowned manufacturer. • Adjustable optic. • GFR PA6.6 terminal block. • M20 Cable Gland. • Installation work has to be carried on according to the enclosed product manual.

Light output 1



1 x LED

Nominal lamp power	3.3 W	LOR	100%
Lamp flux	370 lm	ULOR	7%
Luminous efficacy	112 lm/W	Total flux	370 lm
CCT	3000 K	Total power	3.3 W
CRI	80		

Mounting mode

Standing / Bollard, Floor mounted

Shape and measurements

Length: 0.59 in
Width: 1.63 in
Height: 1.57 in

Adjustability

Free

Electric

System power: 3.3 W
Appliance Class: III

Protection

IP: 66
IK: 06