Product data sheet

UNISTREET GEN2 BGP281 T25 1 XLED59-4S/830 DM12
BGP281
PHILIPS



The easy way to ledify your road lighting – UniStreet gen2 Designed for large-scale ledification projects, the UniStreet gen2 is the ideal 1:1 luminaire replacement for municipalities. Thanks to its high efficiency and low initial cost, the UniStreet gen2 luminaire enables a fast payback and significant savings in terms of energy consumption within a short period of time. The ease of installation and maintenance is enabled by the Philips Service tag and the Philips SR (System Ready) socket makes it future-ready and you can pair this luminaire with lighting control and software applications such as Interact City. Available with a number of different optics and lumen packages that can even be tuned further to fit exact project requirements, UniStreet gen2 is a true point-to-point replacement solution for conventional light sources. The compact luminaire, using high-quality materials is also easy to dismantle and recycle at the end of its lifetime.

Light output 1



1 x LED

Nominal lamp power	48 W	LOR	87%
Lamp flux	6000 lm	Total flux	5236 lm
Luminous efficacy	109 lm/W	Total power	48 W
CCT	3000 K		
CRI	80		

Mounting mode

Pole top mounted

Shape and measurements

Length: 18.70 in
Width: 9.13 in
Height: 5.79 in

Electric

System power: 48 W