Product data sheet


POLE MOUNTED LUMINAIRE RESIDENZA-2 ZERO M5 16LED 3000K
88.00900.0VXXX
HESS



IP 65


Protective cover made of PC glass. Luminaire rests on four aluminium rods. Cylindrical luminaire body made of cast aluminium, universal holder for poles with spigot 60.3 - 82.5 mm. Luminaire enclosure made of PC, clear. Diameter 200mm. ULOR of 0%, complies with the Dark Sky Standard. Rods and internal parts uniformly painted, dark anthracite textured (similar to DB 703/Gris 2900 sablé)

Light output 1




1 x LED

Nominal lamp power	18 W	LOR	100%
Lamp flux	2243 lm	Total flux	2243 lm
Luminous efficacy	125 lm/W	Total power	18 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	33.9 W	LOR	100%
Lamp flux	4331 lm	Total flux	4331 lm
Luminous efficacy	128 lm/W	Total power	33.9 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	31.6 W	LOR	100%
Lamp flux	4049 lm	Total flux	4049 lm
Luminous efficacy	128 lm/W	Total power	31.6 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	29.4 W	LOR	100%
Lamp flux	3763 lm	Total flux	3763 lm
Luminous efficacy	128 lm/W	Total power	29.4 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	27.1 W	LOR	100%
Lamp flux	3471 lm	Total flux	3471 lm
Luminous efficacy	128 lm/W	Total power	27.1 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	24.8 W	LOR	100%
Lamp flux	3173 lm	Total flux	3173 lm
Luminous efficacy	128 lm/W	Total power	24.8 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	20.2 W	LOR	100%
Lamp flux	2561 lm	Total flux	2561 lm
Luminous efficacy	127 lm/W	Total power	20.2 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	15.7 W	LOR	100%
Lamp flux	1916 lm	Total flux	1916 lm
Luminous efficacy	122 lm/W	Total power	15.7 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	13.4 W	LOR	100%
Lamp flux	1583 lm	Total flux	1583 lm
Luminous efficacy	118 lm/W	Total power	13.4 W
CCT	3000 K		
CRI	80		



1 x LED

Nominal lamp power	11.1 W	LOR	100%
Lamp flux	1237 lm	Total flux	1237 lm
Luminous efficacy	111 lm/W	Total power	11.1 W
CCT	3000 K		
CRI	80		



1 x LED

Nominal lamp power	22.5 W	LOR	100%
Lamp flux	2868 lm	Total flux	2868 lm
Luminous efficacy	127 lm/W	Total power	22.5 W
CCT	3000 K		
CRI	80		

Mounting mode

Pole top mounted

Shape and measurements

Length: 8.03 in
Width: 8.03 in
Height: 26.41 in

Adjustability

Fixed

Electric

System power: 11.1-33.9 W

Protection

IP: 65