Product data sheet


CIRCULAR INWARD Ø900 RECESSED
CD5K-00X9AZOU14
LEDSC4



IP 20

LedsC4 Circular Inward ø900 Recessed CD5K-00X9AZOU14V1 Pendant for indoor use. For uplighting and downlighting. Structure finish: White. Diffuser material: Polycarbonate. Diffuser finish: Opal. Warranty: 5 Years. Product net weight (Kg): 5 Product width or diameter (mm): 916 Product height (mm): 3000 Ø of the hole for recessing (mm): 100 Class 1. IP: IP20. LED. No. of lampholders or LEDs: 1. Driver brand: MEANWELL. Maximum power of light source: 49.6W. Colour temperature: 4000K. Colour rendering index: 90. MacAdam Steps: 3. Hours of life: 50.000h L80B20. UGR: 8.3. Photobiological risk: RG1. Real flux (lm): 2971. Real lm/W: 56. Voltage / frequency range: 90-305/50-60Hz. Voltage: 2,8. Equipment included: Yes. Total power: 53. Power factor: 0.90. Dimmable equipment included: ON-OFF.

Light output 1



1 x LED

Nominal lamp power	53 W	LOR	100%
Lamp flux	2971 lm	ULOR	50%
Luminous efficacy	56 lm/W	Total flux	2968 lm
CCT	4000 K	Total power	53 W
CRI	90		

Mounting mode

Pendant, Table luminaire

Shape and measurements

Length: 35.43 in
Width: 35.43 in
Height: 1.18 in

Adjustability

Fixed

Electric

System power: 53 W
Appliance Class: I

Protection

IP: 20