

Product data sheet

FRAME WHITE 8W LED 4000K RA>80
5046605571
SG ARMATUREN



The Frame light fitting features a modern, stylish design that is great whether it is used indoors or outdoors. It can be mounted on ceilings and walls. Made using pressure-moulded, powder-coated aluminium with a black, white or graphite surface. The shade is produced from UV-stabilised opal polycarbonate. The Frame family is available in round, square and rectangular shapes in a range of sizes. Versions featuring sensors, twilight switches and emergency lights are available. Easy to install, two inputs/outputs for cables, with the option for either hidden or visible cabling. 10 year corrosion guarantee, IP65 protection rating, impact strength IK10. Light distribution Direct Light technic LED (exchangeable) 8W 3000K or 4000K Ra>80 SDCM 4 L80/B20 >50,000 hrs at Ta=25°C Control/Dimming Phase cut-off On/off (Sensor/Twilight) Protection Class II IP65 IK10 Energy and approvals A CE Materials and finish Housing: Aluminium Colour: Black (RAL 9004), Graphite (RAL 7024) or White (RAL 9003) Optics: Polycarbonate (PC) Mounting/Connection Surface Screwless terminal block

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	8 W	CRI	80
Total flux	730 lm	LOR	100%
Luminous efficacy	91 lm/W	Total power	8 W

Mounting mode

Ceiling mounted, Wall mounted

Shape and measurements

Length: 12.60 in
Width: 7.09 in
Height: 3.03 in

Adjustability

Fixed

Design

Color of housing: Black, Anthracite / graphite, White

Electric

System power: 8 W
Appliance Class: II

Protection

IP: 65
IK: 10