# Product data sheet


FLUMO60-S 228S-260K-120EE/840, W
228S-260K-120EE/840
HALLA



IP 20 IK 01


228S-260K-120EE/840, W Luminaire surface/suspended Material of luminaire: Colour of luminaire: Shape of luminaire: Rounded Size: 632 x 60 x 65 mm Type of installation: Surface, Suspended Distribution: Direct Optics type: Opal diffuser Protection class: I Voltage: 220-240V

## Light output 1 (integrated)




| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 1.95 W | CRI | 80 |
| Total flux | 223 lm | LOR | 100% |
| Luminous efficacy | 114 lm/W | ULOR | 2% |
| | | Total power | 1.95 W |

## Light output 2 (integrated)




| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 1.95 W | CRI | 80 |
| Total flux | 223 lm | LOR | 100% |
| Luminous efficacy | 114 lm/W | ULOR | 2% |
| | | Total power | 1.95 W |

## Light output 3 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 1.95 W | CRI | 80 |
| Total flux | 223 lm | LOR | 100% |
| Luminous efficacy | 114 lm/W | ULOR | 2% |
| | | Total power | 1.95 W |

Light output 4 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 1.95 W | CRI | 80 |
| Total flux | 223 lm | LOR | 100% |
| Luminous efficacy | 114 lm/W | ULOR | 2% |
| | | Total power | 1.95 W |

### Mounting mode

Pendant, Ceiling mounted

### Shape and measurements

Length: 5.91 in
Width: 2.36 in
Height: 2.56 in

### Adjustability

Fixed

### Electric

System power: 7.8 W
Appliance Class: I

### Protection

IP: 20
IK: 01