


Product data sheet

LIGHT CUT SPOT MODULE
09.0084/HI PAR 51/35W/10°25°40°
FLOS




Spotlight to be installed on Light Cut system. Integrated electronic control gear 220/240 – 50/60Hz.


Light output 1



1 x Metal halide lamp			
Nominal lamp power	35 W	Socket	Gx10
Lamp flux	2297 lm	LOR	67%
Luminous efficacy	66 lm/W	Total flux	1539 lm
CCT	3000 K	Total power	35 W
CRI	80		



1 x Metal halide lamp			
Nominal lamp power	35 W	Socket	Gx10
Lamp flux	2194 lm	LOR	61%
Luminous efficacy	63 lm/W	Total flux	1329 lm
CCT	3000 K	Total power	35 W
CRI	80		



1 x Metal halide lamp			
Nominal lamp power	35 W	Socket	Gx10
Lamp flux	2441 lm	LOR	63%
Luminous efficacy	70 lm/W	Total flux	1533 lm
CCT	3000 K	Total power	35 W
CRI	80		

Mounting mode

Ceiling mounted

Electric

System power: 35 W
Appliance Class: I

Shape and measurements

Height: 3.50 in

Diameter: 2.20 in

Adjustability

Rotatable

Protection

IP: 20