


Product data sheet

REC IP68 LIGHT 1X 3WATT MONO - WW - ASYM
L13616A
PROLED (MBN GMBH)



The PROLED REC IP68 LIGHT is suitable as underwater spotlight for fountains, pools, ponds, water gardens etc. for atmospheric or underwater lighting. - dimmable and controllable via DMX 512, DALI, KNX, 1-10V, CASAMBI, RF by MULTI power supplies or PRO CONTROLLER - incl. PVC plastic mounting sleeve - The mounting sleeve for REC IP68 LIGHT 1x 3 Watt is not waterproof. The sealing must be installed on-site. This IP68 luminaire can not be operated out of water for over 15 minutes (cooling).

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	3 W	CRI	80
Total flux	170 lm	LOR	100%
Luminous efficacy	57 lm/W	Total power	3 W

Mounting mode

Wall recessed

Shape and measurements

Height: 3.70 in
Diameter: 2.68 in
Weight: 0.7 kg

Adjustability

Fixed

Electric

System power: 3 W
Controller: Dimmable 1..10V, DMX, DALI
Appliance Class: III

Protection

IP: 68
IK: 06

Other operating numbers

Ambient temperature range: 14...104°F