

# Product data sheet

LSR8B/LSRWW8B LED 8" ROUND CYLINDERS

LSR8B10D010 EC8B109730 8LBS0LI

COOPER LIGHTING




IP  
47

Distributions: narrow, medium and wide beams, Mounting: high bay/low bay ceiling, wall, stem or aircraft cable, Spun aluminum housing; Spun aluminum reflectors, 5 color temperatures: 2700K, 3000K, 3500K, 4000K and 5000K CCT, CRI: 80, 90 or 97; D2W™ option from 3000K to 1850K, Lumens: 1,000-15,000; W2N Tunable White 2700K-6500K or 2000K-5000K, Colors: Matte Black, White, Bronze and Silver paint finishes, Standard 0-10V dimming down to 1%, ENERGY STAR® qualified, 5-year warranty, Integral or remote driver options

---

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	10.2 W	CRI	100
Total flux	939 lm	LOR	100%
Luminous efficacy	92 lm/W	Total power	10.2 W

---

## Mounting mode

Ceiling recessed

## Electric

System power: 10.2 W

## Shape and measurements

Length: 3.94 in

## Protection

Width: 3.94 in

IP: 47

Height: 3.94 in

## Adjustability

Fixed