
Product data sheet


LP SLIM BOX RECESSED BLACK LED 3000K 25W PRISM
91792-1006
LOUIS POULSEN



IP 20

LP Slim Box Recessed Design by: Louis Poulsen A/S Concept: The product family shares a high-efficiency light unit framed in a rectangular housing. The recessed variants emit downwardly directed light, while the suspended and surface-mounted variants provide a combination of primarily downwardly directed and indirect light. Choosing between opal diffusers or micro-prismatic solutions, the glare and visual expression can be balanced as desired. The light egress emphasizes the design detail in the housing, ensuring a comfortable and subtle yet distinct design. Finish: White or black, powder coated or clear lacquered, pickled aluminium. Materials: Frame/Housing: Die cast Aluminium, Light Engine bottom: Acrylic (Opal or clear). Light Engine top: Acrylic opal. Mounting: Ceiling thickness: 1–40 mm. Cutout dimensions: 678 x 138 mm. Maximum cutout dimension: 683 x 143 mm. Built-in height: minimum 80 mm. Mounting bracket included. Optional wire for alternative installation. Looping: Approved, max. 5 x 1.5 mm². Integrated driver. Sizes and weights: Width x Height x Length (mm) 150 x 12 x 689 Max 3.8 kg Class: Ingress protection IP20. Electric shock protection I.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	25 W	CRI	90
Total flux	2288 lm	LOR	69%
Luminous efficacy	92 lm/W	Total power	25 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 27.17 in
Width: 5.91 in
Height: 1.73 in

Adjustability

Fixed

Electric

System power: 25 W
Appliance Class: I

Protection

IP: 20