
Product data sheet

TOWNTUNE CENTRAL POST-TOP DTC BDP262 1 XLED24-4S/740 DW10
BDP262
PHILIPS



Philips TownTune Central Post Top - Extending the home feel onto the street Designed to enhance existing and scalable urban spaces, the Philips TownTune family offers all the latest lighting innovations in terms of performance, quality of light and connectivity. The family consists of four solutions: a Central Post Top (CPT), an Asymmetric Spigot Post Top / Side Entry version (ASY), a version with an extending Lyre post top bracket (Lyre), and a Central Post Top with a Conical Comfort Bowl (CCB). Each TownTune luminaire can be customized with a choice of different shapes on top of the housing, plus there's the option to add a decorative ring, which comes in two colors (excluding CCB). Design options that enable you to create your very own lighting signature and bring a distinctive identity to districts and cities. In addition, every luminaire in the TownTune family is uniquely identifiable, thanks to the Signify Service tag app. By simply scanning a QR code, placed inside the door of the mast or directly on the luminaire, you can instantly access the configuration of the luminaire. This makes maintenance and programing operations faster and easier and enables you to create your digital library of lighting assets and spare parts. TownTune also uses the Philips LEDGINE-O lighting platform, ensuring you always have the right amount and direction of light on your street. Furthermore, thanks to being system ready (SR), TownTune is also future proof. A solution that's ready to be paired with both standalone and advanced control and lighting software applications such as Interact City.

Light output 1



1 x LED

Nominal lamp power	15.6 W	LOR	76%
Lamp flux	2400 lm	Total flux	1826 lm
Luminous efficacy	117 lm/W	Total power	15.6 W
CCT	4000 K		
CRI	70		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 24.41 in
Width: 24.41 in
Height: 1.26 in
Weight: 2.15 kg

Design

Material impression: Stainless steel
Color of housing: White

Electric

System power: 15.6 W

Protection

Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: 14...122°F