Product data sheet

LINEDO_4,5M_90_11111111
954590.833.776.024
RZB



IP 54 IK 03

LINEDO, 218 W, 40400 lm, 830, black, DALI Continuous line luminaire, L 4547 B 58 H 76

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	27.3 W	CRI	80
Total flux	5050 lm	LOR	100%
Luminous efficacy	185 lm/W	Total power	27.3 W

Light output 2 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	27.3 W	CRI	80
Total flux	5050 lm	LOR	100%
Luminous efficacy	185 lm/W	Total power	27.3 W

Light output 3 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	27.3 W	CRI	80
Total flux	5050 lm	LOR	100%
Luminous efficacy	185 lm/W	Total power	27.3 W

Light output 4 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	27.3 W	CRI	80
Total flux	5050 lm	LOR	100%
Luminous efficacy	185 lm/W	Total power	27.3 W

Light output 5 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	27.3 W	CRI	80
Total flux	5050 lm	LOR	100%
Luminous efficacy	185 lm/W	Total power	27.3 W

Light output 6 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	27.3 W	CRI	80
Total flux	5050 lm	LOR	100%
Luminous efficacy	185 lm/W	Total power	27.3 W

Light output 7 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	27.3 W	CRI	80
Total flux	5050 lm	LOR	100%
Luminous efficacy	185 lm/W	Total power	27.3 W

Light output 8 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	27.3 W	CRI	80
Total flux	5050 lm	LOR	100%
Luminous efficacy	185 lm/W	Total power	27.3 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 2.28 in
Width: 179.02 in
Height: 2.99 in

Adjustability

Fixed

Electric

System power: 218.4 W

Protection

IP: 54
IK: 03