
Product data sheet

ATHLON OPTIC AREA LIGHT / DOUBLE SIDED


7259-I-3-898-XX

UNILAMP




ATHLON is a series of mini floodlights with wide beam asymmetrical and bi-symmetrical light distribution. It operates with High Power LED module which is attached on aluminium body as a heat sink. The Alanod Miro reflectors used in this luminaire are designed by Photopia highend lighting engineering software. The calibrated aiming unit provides accuracy of the light distribution on the illuminated surface. The range of accessories such as ground mount spike, tree strap and pole clamping unit makes it a dynamic floodlight choice. ATHLON is suitable to light up small to medium sized objects or areas such as signage boards, ceiling, building facades, etc.

Light output 1



1 x LED			
Nominal lamp power	25 W	LOR	77%
Lamp flux	3090 lm	Total flux	2367 lm
Luminous efficacy	124 lm/W	Total power	28 W
CCT	4000 K		
CRI	80		

Light output 2



1 x LED

171220			
Nominal lamp power	25 W	LOR	77%
Lamp flux	3090 lm	Total flux	2367 lm
Luminous efficacy	124 lm/W	Total power	28 W
CCT	4000 K		
CRI	80		

Mounting mode	Electric	
Pole top mounted, Pole integrated	System power: 56 W	
Shape and measurements	Appliance Class: I	
Length: 9.67 in	Protection	
Width: 4.13 in	IP: 66	
Height: 9.23 in	IK: 07	
Adjustability		

Created by luminaires.dialux.com (8 May, 2024)

Rotatable, Tiltable