
Product data sheet

VILLA LED GEN2 BDP768 FG T25 1 XLED24-4S/722 DM31 MK-BK
BDP768
PHILIPS



Iconic Iberian four-sided luminaire Villa LED gen2 retains the specific proportions and shape of the traditional four-sided luminaires originally used in 19th century in Madrid. It allows a remarkable balance between performance and heritage preservation. Now widely used across the Iberian Peninsula, Villa LED gen2 is suitable for lighting historical environments and traditional towns and villages. Thanks to the builtin Philips Ledgine optimized LED platform, and the wide range of available application-tailored optics, Villa LED gen2 delivers the right amount light and in the right direction on your street, enabling further energy savings. The luminaire comes with one or two Philips SR (System Ready) sockets, which makes the luminaire future ready. What this means is that Villa LED gen2 is ready to be paired with both standalone and advanced control and lighting software applications such as Interact City from Signify. Next to this, each individual luminaire is uniquely identifiable, thanks to the Philips Service tag application. With a simple scan of a QR code, placed on the inside of the mast door or directly on the luminaire, you gain instant access to the luminaire configuration, making maintenance and programming operations faster and easier, and enabling you to create your digital library of lighting assets and spare parts. Villa LED gen2 can also be equipped with our dedicated light recipe that preserves a dark night sky.

Light output 1



1 x LED

Nominal lamp power	20.5 W	LOR	69%
Lamp flux	2400 lm	Total flux	1659 lm
Luminous efficacy	81 lm/W	Total power	20.5 W
CCT	2200 K		
CRI	70		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 15.75 in
Width: 15.75 in
Height: 29.69 in

Electric

System power: 20.5 W