


Product data sheet

MODULE_60_DIAS_26W_WARM_SPOT
80621201_
PETRIDIS



- Version with LED Module. - Outer adjustable ring from die-cast aluminium. - Inner ring for easy lamp replacement. - 26W power consumption driven at 700mA. - Heatsink from aluminium profile. - Efficient thermal management. - Operation life: 50,000 hours with efficiency > 80% of the initial luminous flux (L80B10). - Connection for operation with Constant Current. - CRI: min. 80 / SDCM: 3 - Luminous Efficacy: 26W: 4000 K: 154 Lm/Watt 26W: 3000 K: 148 Lm/Watt Upon request: Available with highest colour rendering index (CRI)

Light output 1



1 x LED			
Nominal lamp power	26 W	LOR	81%
Lamp flux	3729 lm	Total flux	3016 lm
Luminous efficacy	143 lm/W	Total power	26 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 5.31 in
Diameter: 5.91 in

Adjustability

Fixed

Design

Material impression: Aluminum

Electric

System power: 26 W
Controller: Dimmable 1..10V, DALI
Appliance Class: III

Protection

IP: 20
Designation labels: CE