


Product data sheet

TRIANGLE 5 STREET AND AREA LIGHTING LUMINAIRES


TR-96141-ME-W40

LIGMAN



- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear toughened glass - Surge protection 10 kV

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	37.3 W	CRI	80
Total flux	4598 lm	LOR	100%
Luminous efficacy	123 lm/W	Total power	37.3 W

Mounting mode

Wall mounted, Pole top mounted

Shape and measurements

Length: 53.94 in

Width: 12.68 in

Height: 3.54 in

Weight: 27.5 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 37.3 W

Voltage: 230 V AC

Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

Protection

IP: 54

IK: 07

Surface temperature: 40°C