
Product data sheet

LINE 50 QUAD
LQ50H-159402-HXXXO
LUX-IT




pendant mounted dir-indir LED luminaire;

Light output 1 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	66.55 W	CRI	90
Total flux	8293 lm	LOR	100%
Luminous efficacy	125 lm/W	Total power	66.55 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	66.55 W	CRI	90
Total flux	8293 lm	LOR	100%
Luminous efficacy	125 lm/W	Total power	66.55 W

Light output 3 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	66.55 W	CRI	90
Total flux	8293 lm	LOR	100%
Luminous efficacy	125 lm/W	Total power	66.55 W

Light output 4 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	66.55 W	CRI	90
Total flux	8293 lm	LOR	100%
Luminous efficacy	125 lm/W	Total power	66.55 W

Mounting mode

Pendant

Shape and measurements

Length: 59.06 in
Width: 59.06 in
Height: 3.15 in

Adjustability

Fixed

Electric

System power: 266.2 W

Protection

IP: 20
Designation labels: CE