

Product data sheet

BRISA-L2WG6-LC-A2-32LED-4000K-7560LM-49.6W
LIGHTRONICS




IP
66

IK
10

BRISA FUNCTIONALLY COMPLETE From residential streets to access roads: the BRISA makes it possible to illuminate the entire living environment with a single luminaire line. The BRISA has specific variants for crossings, cycle paths and for protecting flora and fauna. This versatility makes the BRISA line suitable for business parks, industrial estates, ecological zones, parking spaces, large car parks, cycle paths, roundabouts, holiday parks, footpaths and residential areas. All the luminaires in the BRISA line are impact-resistant (IK 10) and waterproof (IP 66).

Light output 1



32 x LED			
Nominal lamp power	1.55 W	LOR	100%
Lamp flux	236 lm	ULOR	3%
Luminous efficacy	152 lm/W	Total flux	7552 lm
CCT	4000 K	Total power	49.6 W
CRI	70		

Mounting mode

Pole integrated, Pole top mounted

Electric

System power: 49.6 W

Shape and measurements

Length: 23.62 in

Width: 9.45 in

Height: 5.12 in

Protection

IP: 66

IK: 10

Adjustability

Fixed

Design

Material impression: Aluminum

Color of housing: Black, Anthracite / graphite, Silver gray