


Product data sheet

SAFESITE LED LOW BAY 4000 LUMENS, ULTRA WIDE DISTRIBUTION, DIFFUSED POLYCARBONATE DOME LENS
LEDLUC24XXXXXN
DIALIGHT



SafeSite LED Low Bay 4,000 Lumens 42 Watts 100-277V AC, 120-250V DC Cool White, 80CRI Diffused Polycarbonate Dome Lens Class I, Div. 2, Groups A,B,C,D Class II, Div. 1, Groups E,F,G Class II. Div. 2, Groups F,G Class III UL 8750 UL 1598/A (wet locations) CSA C22.2 No. 250.0-08 NEMA 4X IK10 Ultra Wide Distribution IP66/67 LM79 Tested IES File

Light output 1 (integrated)



Lamp type	LED	CCT	5181 K
Nominal lamp power	38.6 W	CRI	80
Total flux	3922 lm	LOR	100%
Luminous efficacy	102 lm/W	Total power	38.6 W

Mounting mode

Pendant

Shape and measurements

Length: 15.94 in
Width: 15.94 in
Height: 8.27 in

Adjustability

Rotatable, Tilttable

Electric

System power: 38.6 W
Appliance Class: I

Protection

IP: 66
IK: 10

Other operating numbers

Ambient temperature range: -40...149°F