

Product data sheet


G2 EVO - 11 W - IP66/IK10 - BLACK REFLECTOR - WALLWASH - 4000K - EMERGENCY
EGUX11WWB
THORLUX LIGHTING



IP
66

Recessed circular LED downlighters. The G2 Evo is a compact, stylish recessed circular downlighter, engineered for efficient performance. Delivering efficacy of up to 145 LL/CW, the G2 Evo is available in black or white finishes, with 3000 K or 4000 K colour temperatures. Featuring a die-cast aluminium body with an injection-moulded polycarbonate reflector, this luminaire is rated IP40 as standard, with IK10 impact-rated/IP66 versions available for more demanding applications. G2 Evo is manufactured from 43% recycled materials, and has achieved a TM66 score of 2.8 (LIA/CIBSE TSD-012 verified), confirming an 'excellent' level of product circularity. Applications: reception areas, retail, public areas, and toilets.

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	13 W	CRI	80
Total flux	1555 lm	LOR	100%
Luminous efficacy	120 lm/W	Total power	13 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 2.44 in
Diameter: 5.31 in

Adjustability

Fixed

Electric

System power: 13 W

Information regarding emergency functions

Emergency lighting only
Emergency sign: N/A

Protection

IP: 66