
Product data sheet

DROP 22 S/EW 60W IAA WH-87 | IAA
004961_IAA
PERFORMANCE IN LIGHTING



Part number: 004961. Serie: DROP. Wall and ceiling mounted luminaire for indoor and outdoor, comprising: Housing manufactured from technopolymer. Pressed glass diffuser, internally coated, and matt finished outside . Class II. Aluminium reflector. Technopolymer silicone sealing gasket. Side entry for 20 mm conduits (drill out holes in housing arrangement). Chromed steel spring locks to secure the diffuser to housing. Self-adhesive pictograms available as accessory (ordered separately) . Design by ROBERTO FIORATO. Product data | ETIM Group: EG000027. ETIM Class: EC002892. General information | Lampholder: E27. Luminaire wattage [W]: 1x60 W. Colour / Finishing: WH-87 / White / Textured. IP degree of protection: IP55. IK06 1J xx3. Protection class: II. Optic: S/EW - Symmetric Extra-Wide. Net weight [kg]: 1.582. Overall diameter [mm]: 228. Overall width [mm]: 95. Mechanical features | Shape: Round 150 x 300 mm. Housing material: Plastic. Diffuser material: Glass. Glow wire test [°C]: 750 °C. Electrical features | Installation | Application area: PROFESSIONAL OUTDOOR. Mounting type: Bulkheads. Min. ambient temperature [°C]: -30. Max. ambient temperature [°C]: 25. Installation without tools. Side cable entry. Suitable for sea front installation. Light features | Lamps: 1. ILCOS: IAA. Certifications | CE certified. EAC certified. UKCA certified. RCM certified. Mountable on normally inflammable surfaces.

Light output 1



1 x General service incandescent lamp

Nominal lamp power	60 W	LOR	46%
Lamp flux	710 lm	ULOR	5%
Luminous efficacy	12 lm/W	Total flux	324 lm
CCT	2700 K	Total power	60 W
CRI	100		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 8.98 in
Width: 8.98 in
Height: 3.74 in

Adjustability

Fixed

Electric

System power: 60 W
Appliance Class: I

Protection

IP: 55
IK: 06
Designation labels: CE, F