


Product data sheet


ISKRA LED 36 PROG 2700K SP
2132132/1/SP/10KV
ROSA



IP
66

Programmable version of the ISKRA LED luminaire. It is used, among others, on urban roads, residential streets, bicycle paths, pedestrian routes and in parks. Made of aluminium alloy – in standard version anodised in inox and black. Luminaire is mounted on an extension arm with a \varnothing 60 x 90 mm ending. It has a protection class of IP 66 for the optical part and the power input system. The operating temperature range is from -40°C to $+55^{\circ}\text{C}$. The expected service life is L90B10 - 100,000 h. The input voltage frequency is 50/60Hz. Power factor ≥ 0.95 . Equipped with 12 LEDs. It is possible to connect the luminaire to an external control system via the DALI interface (optional support for an analogue 1-10V signal).

Light output 1



1 x LED

Nominal lamp power	40 W	LOR	95%
Lamp flux	5550 lm	Total flux	5285 lm
Luminous efficacy	139 lm/W	Total power	40 W
CCT	2700 K		
CRI	70		

Mounting mode

Pole top mounted

Shape and measurements

Length: 15.98 in

Width: 3.62 in

Height: 2.60 in

Adjustability

Fixed

Electric

System power: 40 W

Protection

IP: 66