


Product data sheet

APOLLO G2 DALI 1260MM PO 1X21W 080° 3700LM
9480029M
PRACHT



Food-certified Reflector luminaire APOLLO G2 DALI 1260mm PO 1x21W 080° 3700lm 4.000K, class I, with TW 5x2,5mm²+2x1,5mm². New generation of the APOLLO damp-proof reflector luminaire. Swiveling reflectors. Acid and alkali resistant. IP65 protection class. Ideal for industry and logistics. 5-year warranty. Item number: 9480029m GTIN: 4018098416975 Technical details/specification: Cover made of PO; Housing made of GRP polyester White RAL 9010; 220–240 V 0/50/60 Hz; Energy efficiency class B; Number of light sources / LED rows: 1; IP65; Through-wiring in mm²: 5x2,5+2x1,5; Dimensions: LxWxH: 1260mm x 105mm x 152mm; Diameter: mm

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	21 W	CRI	80
Total flux	3700 lm	LOR	100%
Luminous efficacy	176 lm/W	Total power	21 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 49.61 in
Width: 4.13 in
Height: 5.98 in
Weight: 2.7 kg

Adjustability

Tiltable

Design

Color of housing: White

Electric

System power: 21 W
Appliance Class: I

Protection

IP: 65
IK: 08

Other operating numbers

Ambient temperature range: -4...113°F