# Product data sheet


IL2 2L80 4ER OA
IN-LINE
DEXTRA



IP 20

In-Line - 2000mm, IP20, C84 Continuous Run luminaire with Opal lens optic and quick electrical connection with plug and socket system. Options: LE3 - Lithium Emergency LS3 - Lithium Selftest LA3 - Lithium Autotest LSTR - Lithium Emergency Reacta-Link CB - Please specify 50v, 110v or 230v when ordering S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) H - High Frequency Dimming (Analogue 1-10v) Continuous Run options: 6TW - 6 Pole 1.5mm2 Wiring Loom c/w Male/Female Connectors IL2 4P 5M START - 4 Pole 5m Starter Lead IL2 6P 5M START - 6 Pole 5m Starter Lead IL2 5M SUSP 15KIT - 5m Suspension Kit for 15mm Exposed Tee Bar IL2 5M SUSP 24KIT - 5m Suspension Kit for 24mm Exposed Tee Bar IL2 5M SUSP GPLKIT - 5m Suspension Kit for Purlin IL2 ENDCAP KIT - Pair of Finishing Endcaps

## Light output 1 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 47.88 W | CRI | 80 |
| Total flux | 6848 lm | LOR | 100% |
| Luminous efficacy | 143 lm/W | Total power | 47.88 W |

### Mounting mode

Pendant

### Shape and measurements

Length: 77.24 in
Width: 1.81 in
Height: 2.20 in

### Adjustability

Fixed

### Electric

System power: 47.88 W

### Protection

IP: 20
Designation labels: CE