

# Product data sheet

POZZO I OPAL LED 350 840 CLO  
24284-520  
FAGERHULT



Installation Recessed mounting in ventilated or unventilated ceilings. Fixing brackets included with luminaire. An assembly plate should be used when installing in soft tile ceilings. The luminaire must not be covered with insulation. For further details please refer to the assembly instructions. Connection Connection in driver box. The driver box can be positioned next to the luminaire. Snap-in terminal block 3x1.5 mm<sup>2</sup> (5x1.5 mm<sup>2</sup> where dimming is required). Through-wiring- possible. Design Luminaire in white (RAL 9016) structured finish. Luminaire housing of enamelled deep drawn aluminium. Diffuser of opalised acrylic. Dimming CLO (Constant Light Output) maintains the correct light from the luminaire for the duration of its service life.

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	13 W	CRI	80
Total flux	1321 lm	LOR	100%
Luminous efficacy	102 lm/W	Total power	13 W

## Mounting mode

Ceiling recessed

## Shape and measurements

Height: 6.10 in  
Diameter: 15.08 in

## Adjustability

Fixed

## Design

Color of housing: White

## Electric

System power: 13 W

## Protection

IP: 20