

Product data sheet

OFFICE LIGHTING
V1-A0-00350-01PR0-4003565 A350 2.0 IP40 1195X295X50 MM 35W 6500K PRISM
VARTON




IP
40

IK
01

Versatile office luminaire. Stainless steel housing with white powder coating. Application: administrative facilities, lobbies. Recessed and surface-mounted. Compatible with the Armstrong Prelude 24 suspended ceiling systems. Input voltage (AC, 50Hz), V: 176...264 AC frequency, Hz: 50 Flicker, %: 2 Climatic modification and category of placement: YXJ4 Height/depth, mm: 50 Length, mm: 1 195 Protection class: I Ingress protection (IP): IP40 Impact resistance: IK01 Width, mm: 295 Power factor: 0,95 https://www.varton.ru/products/ofisnoe-osveshchenie/a-seriya-2-0/a350-2-0-ip40-ofis-1195-295-analog-2-36/svetodiodnyy-svetilnik-var-ton-a350-2-0-ofisnyy-vstraivaemyy-nakladnoy-35-vt-6500-k-1195kh295kh50-mm-_5/

Light output 1



1 x LED			
Nominal lamp power	35 W	LOR	100%
Lamp flux	4730 lm	Total flux	4730 lm
Luminous efficacy	135 lm/W	Total power	35 W
CCT	6500 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 47.05 in
Width: 11.61 in
Height: 1.97 in

Adjustability

Fixed

Electric

System power: 35 W

Protection

IP: 40
IK: 01