


Product data sheet

PH 3/2 TABLE E14 LED 2700K 5W
5744162801
LOUIS POULSEN



PH 3/2 Table Design : Poul Henningsen Concept : The fixture is designed based on the principle of a reflective three-shade system, which directs the majority of the light downwards. The shades are made of hand-blown opal three-layer glass, which is glossy on top and sandblasted matte on the underside, giving a soft and diffuse light distribution. Finish : Black chrome plated or high lustre chrome plated. White opal glass. Material : Shades: Mouth-blown white opal glass. Top plate: Black chrome plated or high lustre chrome plated, spun brass. Base: Black chrome plated or high lustre chrome plated, brass. Stem: Black chrome plated or high lustre chrome plated, brass. Mounting : Cable type: Plastic cord with plug. Cable length: 2.1m. Light control: In-line switch on cord. Class : Ingress protection IP20. Electric shock protection II w/o ground. Weight : Max. 2.5kg.

Light output 1



1 x LED			
Nominal lamp power	5 W	LOR	38%
Lamp flux	470 lm	ULOR	15%
Luminous efficacy	36 lm/W	Total flux	178 lm
CCT	2700 K	Total power	5 W
CRI	80		

Mounting mode

Table luminaire

Shape and measurements

Height: 18.58 in
Diameter: 11.42 in

Adjustability

Fixed

Electric

System power: 5 W
Appliance Class: II

Protection

IP: 20