

# Product data sheet

STICK CONE - LIGHT COLUMN


7212-0-3-781-XX

UNILAMP




STICK is a family of cylindrical-shaped light column and wall luminaire giving symmetrical light distribution on illuminated surfaces. The recommended mounting height is between 3 – 4 meters above ground. It is operated with high power LED. STICK is assembled with anti-glare suppression louvers that direct the light downward onto the illuminated surface. Clear PMMA cover protects the lamp compartment from the ingress of dust and water. It is generally installed in walkways, gardens, parks, commercial areas and open spaces to provide the general lighting from mid-high level. Anchor unit for concrete foundation are is available. spec • Designed, Manufactured and tested according to IEC 60598-1, IEC 60598-2-1 and VDE regulations. • LM6 Die Cast Aluminium and Extruded Aluminium body. • Stainless steel screws. • Nano Ceramic surface conversion. • Double layer coating. • PMMA protective cover. • Post-cured silicone gasket. • High quality LED module and driver. • Anodized aluminium louvers. • GFR PA6.6 Terminal block. • Weather proof grommet. • Pole light pre-wired with outdoor cable. • Installation work has to be carried on according to the enclosed product manual.

## Light output 1



1 x Metal halide lamp			
Nominal lamp power	70 W	Socket	G12
Lamp flux	6600 lm	LOR	22%
Luminous efficacy	94 lm/W	Total flux	1484 lm
CCT	4000 K	Total power	79 W
CRI	94		



1 x Metal halide lamp			
Nominal lamp power	70 W	Socket	G12
Lamp flux	6600 lm	LOR	22%
Luminous efficacy	94 lm/W	Total flux	1484 lm
CCT	3000 K	Total power	79 W
CRI	88		

## Mounting mode

Pole top mounted

## Shape and measurements

Length: 7.40 in

Width: 7.40 in

Height: 134.17 in

## Electric

System power: 79 W

Appliance Class: I

## Protection

IP: 65

IK: 10

Adjustability

Fixed