
Product data sheet

LUMBO S 1400 36º E 63 930 3F
11.2026.2331.63
LUXIONA



Spherical injected steel monoblock spotlights with high quality finishes and an optical system based on highly efficient spotlights. The whole body works as a heat sink, improving the working efficiency of the LED to optimize consumption. The equipment is integrated into the threephase adapter. Assembly: mounted on a three-phase track. The body material is aluminum. Colour - RAL 9003 (white). Dimensions: Ø80 x 105 mm. Weight 0,9 kg. Diffuser: reflector plastic metalized. Beam angle: 36°. Light source type: LED. Colour of the light 3000 K. SDCM=3. CRI>90. Lifetime of LED sources: 60000 h L80/B10. Luminaire luminous flux: 1120 lm. Power of luminaire: 15,1 W. Luminaire's light efficiency: 74,2 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,98. Circuit load capacity: (B10), (B16), (C10), (C16). Operating temperature range: 0 ÷ 30° C. Protection degree: IP20. Protection against electric shock: I.

Light output 1



1 x LED

Nominal lamp power	15 W	LOR	52%
Lamp flux	1121 lm	Total flux	588 lm
Luminous efficacy	75 lm/W	Total power	15 W
CCT	3000 K		
CRI	90		

Mounting mode

Ceiling mounted, Contact rail

Shape and measurements

Height: 3.15 in
Diameter: 3.15 in

Adjustability

Rotatable, Tiltable

Design

Color of housing: White

Electric

System power: 15 W
Appliance Class: I

Protection

IP: 20

Other operating numbers

Ambient temperature range: 32...86°F