


# Product data sheet

PURE 2 DOWNLIGHT  
09.1714/QT-12/20W/35W/50W/75W/100W/21°  
FLOS




Recessed luminaire for indoor application. For very low voltage halogen lamps or standard and discharge lamps. Self-extinguishing ceramic or engineering plastic lamp holders, with single-pole, transparent electric wires with double Teflon insulation.

## Light output 1




### 1 x Halogen low voltage lamp without reflector

|                    |         |             |         |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 100 W   | Socket      | Gy6.35  |
| Lamp flux          | 2200 lm | LOR         | 81%     |
| Luminous efficacy  | 18 lm/W | Total flux  | 1788 lm |
| CCT                | 3000 K  | Total power | 100 W   |
| CRI                | 99      |             |         |




### 1 x Halogen low voltage lamp without reflector

|                    |         |             |         |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 75 W    | Socket      | Gy6.35  |
| Lamp flux          | 1450 lm | LOR         | 81%     |
| Luminous efficacy  | 16 lm/W | Total flux  | 1178 lm |
| CCT                | 2756 K  | Total power | 75 W    |
| CRI                | 99      |             |         |




### 1 x Halogen low voltage lamp without reflector

|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Nominal lamp power | 50 W    | Socket      | Gy6.35 |
| Lamp flux          | 910 lm  | LOR         | 81%    |
| Luminous efficacy  | 15 lm/W | Total flux  | 739 lm |
| CCT                | 3000 K  | Total power | 50 W   |
| CRI                | 99      |             |        |



**1 x Halogen low voltage lamp without reflector**

|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Nominal lamp power | 35 W    | Socket      | Gy6.35 |
| Lamp flux          | 600 lm  | LOR         | 81%    |
| Luminous efficacy  | 14 lm/W | Total flux  | 488 lm |
| CCT                | 3000 K  | Total power | 35 W   |
| CRI                | 99      |             |        |



**1 x Halogen low voltage lamp without reflector**

|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Nominal lamp power | 20 W    | Socket      | E27    |
| Lamp flux          | 300 lm  | LOR         | 81%    |
| Luminous efficacy  | 11 lm/W | Total flux  | 244 lm |
| CCT                | 2756 K  | Total power | 22 W   |
| CRI                | 99      |             |        |

**Mounting mode**

Ceiling recessed

**Shape and measurements**

Length: 5.12 in

Width: 5.12 in

Height: 5.51 in

**Adjustability**

Rotatable, Tilttable

**Electric**

System power: 22-100 W

Appliance Class: I

**Protection**

IP: 20