# Product data sheet

SMART LOTIS 82 LED GE 3000K MEDIUM WHITE STRUC 12441409


MODULAR







Smart lighting family Smart Cake, Smart Lotis and Smart Kup form a new generation of spotlights which combine technical ingenuity with timeless design. This family's styling is based on our most popular designs. In concrete terms, the fittings consist of a module (LED, halogen or discharge) which can be combined with one of three trims to suit your requirements. The new spotlights can be combined with Smart Mask or Smart surface box to form the perfect solution for any interior. Smart Lotis comes with the typical Lotis cup. Choose from a white or black structure.

Light output 1







#### Mounting mode

Ceiling recessed

| 1 x LED            |         |             |        |
|--------------------|---------|-------------|--------|
| Nominal lamp power | 13.4 W  | LOR         | 100%   |
| Lamp flux          | 994 lm  | Total flux  | 989 lm |
| Luminous efficacy  | 74 lm/W | Total power | 13.4 W |
| CCT                | 3000 K  |             |        |
| CRI                | 90      |             |        |
|                    |         |             |        |
|                    |         |             |        |
|                    |         |             |        |
|                    |         |             |        |
| 1 x LED            |         |             |        |
| Nominal lamp power | 6.2 W   | LOR         | 100%   |
| Lamp flux          | 576 lm  | Total flux  | 573 lm |
| Luminous efficacy  | 92 lm/W | Total power | 6.2 W  |
| CCT                | 3000 K  |             |        |
| CRI                | 90      |             |        |
|                    |         |             |        |
|                    |         |             |        |
|                    |         |             |        |
| 1 x LED            |         |             |        |
| Nominal lamp power | 9.2 W   | LOR         | 100%   |
| Lamp flux          | 773 lm  | Total flux  | 769 lm |
| Luminous efficacy  | 84 lm/W | Total power | 9.2 W  |
| CCT                | 3000 K  | ,           |        |
| CRI                | 90      |             |        |
|                    |         |             |        |
|                    |         |             |        |

## Shape and measurements

Height: 0.39 in Diameter: 3.23 in

## Adjustability

Fixed

#### Electric

System power: 6.2-13.4 W Appliance Class: II

## Protection

IP: 20