
# Product data sheet

AMMA Φ80 SERIES LENS TYPE(TRIMLESS)
DD161-1515WW9027-TL
KOIZUMI



We specifically use one diameter across a wide range of power output combined with new optical lens to create various beam angles. With a small ceiling cutout size (Ø80mm). It can be widely used in various space/function such as commercial facility, hospitality and residence enviroment. Light emitting surface is offset to be hidden to reduce glare.

## Light output 1



1 x LED

| | | | |
|---|---|---|---|
| Nominal lamp power | 14 W | LOR | 100% |
| Lamp flux | 1141 lm | Total flux | 1141 lm |
| Luminous efficacy | 82 lm/W | Total power | 14 W |
| CCT | 2700 K | | |
| CRI | 90 | | |

### Mounting mode

Ceiling recessed

### Shape and measurements

Height: 4.06 in
Diameter: 3.54 in

### Adjustability

Rotatable, Tiltable

### Design

Material impression: Matt
Color of housing: White
Designer: Koizumi

### Glare protection

Glare protection: UGR < 19

### Electric

System power: 14 W
Ballast: ECG
Suitable for feed-through wiring
Appliance Class: III

### Protection

IP: 20
Designation labels: CCC, CE

### Other operating numbers

Ambient temperature range: 41...95°F