Product data sheet

NEPTUN INDUSTRY LED 12000 PC-T OPTICS-60 E IP66 21 830 / 1163X115X110MM ZASILANIE PRZELOTOWE 16A
19.4343.9311.21


LUXIONA



IP 66 IK 10

Indoor luminaire. Assembly: directly mounted to ceiling construction or surface mounted on slings. The body material is polycarbonate. Colour - RAL 9006 (grey). Dimensions: 1163 x 115 x 110 mm. Diffuser: PC-T (transparent polycarbonate). The efficiency of the optical system is 89,78%. Beam angle: (C0-C180) / (C90-C270) - 55,4° / 54,8°. Light source type: LED. Colour of the light 3000 K. SDCM=3. CRI>80. Lifetime of LED sources: 90000 h L80/B10. Luminaire luminous flux: 10149,5 lm. Power of luminaire: 67,8 W. Luminaire's light efficiency: 149,7 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 12 (B10), 19 (B16), 19 (C10), 30 (C16). Operating temperature range: -25 ÷ 35° C. Protection degree: IP66. Impact resistant: IK10. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0.

Light output 1



4 x LED

Nominal lamp power	16.95 W	LOR	52%
Lamp flux	2826 lm	Total flux	5927 lm
Luminous efficacy	167 lm/W	Total power	67.8 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 45.79 in
Width: 4.53 in
Height: 4.33 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 67.8 W
Appliance Class: I

Protection

IP: 66
IK: 10

Other operating numbers

Ambient temperature range: -13...95°F