


Product data sheet

HALO CENTRALIZED SUSPENSION DI/ID WHITE 760MM
R48Z076-9016E2840H3S
PLANLICHT




LED HO 4000K 81W 7843lm DALI <https://katalog.planlicht.com/en-us/fam-halo/>

Light output 1 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	10.12 W	CRI	80
Total flux	980 lm	LOR	100%
Luminous efficacy	97 lm/W	ULOR	50%
		Total power	10.12 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	10.12 W	CRI	80
Total flux	980 lm	LOR	100%
Luminous efficacy	97 lm/W	ULOR	50%
		Total power	10.12 W

Light output 3 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	10.12 W	CRI	80
Total flux	980 lm	LOR	100%
Luminous efficacy	97 lm/W	ULOR	50%
		Total power	10.12 W

Light output 4 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	10.12 W	CRI	80
Total flux	980 lm	LOR	100%
Luminous efficacy	97 lm/W	ULOR	50%
		Total power	10.12 W

Light output 5 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	10.12 W	CRI	80
Total flux	980 lm	LOR	100%
Luminous efficacy	97 lm/W	ULOR	50%
		Total power	10.12 W

Light output 6 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	10.12 W	CRI	80
Total flux	980 lm	LOR	100%
Luminous efficacy	97 lm/W	ULOR	50%
		Total power	10.12 W

Light output 7 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	10.12 W	CRI	80
Total flux	980 lm	LOR	100%
Luminous efficacy	97 lm/W	ULOR	50%
		Total power	10.12 W

Light output 8 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	10.12 W	CRI	80
Total flux	980 lm	LOR	100%
Luminous efficacy	97 lm/W	ULOR	50%
		Total power	10.12 W

Mounting mode

Pendant

Shape and measurements

Length: 29.92 in

Width: 29.92 in

Height: 2.44 in

Adjustability

Fixed

Electric

System power: 81 W

Protection

IP: 40

Designation labels: CE