
Product data sheet

RINGO STAR 38MM SUSPENDED - P6
RP6OSE-830M-D3000-U
LIGHTNET




LED pendant luminaire. Direct-indirect or direct-only light distribution. Luminaire body made of aluminium profile with 38mm track width. 6 different diameters from 1000mm to 3500mm. Surface silver, white, graphite, black, champagne or copper coated. Further surface options see Lightnet-Surface-Collection or RAL of your choice. Satin opal diffuser for general lighting with maximum transmittance and homogeneous lighting. Converter integrated in ceiling rose, optionally switchable or dimmable (DALI, Touch-Dim, Casambi). Colour temperatures 2200K, 2700K, 3000K, 3500K, 4000K or 6500K. Binning initial ≤ MacAdam 3. Colour rendering CRI>80 or CRI>90. Height-adjustable central cord suspension or parallel-cord suspension with transparent power supply cable.

Light output 1 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	20 W	CRI	82
Total flux	2601 lm	LOR	100%
Luminous efficacy	130 lm/W	ULOR	45%
		Total power	20 W

Light output 2 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	20 W	CRI	82
Total flux	2601 lm	LOR	100%
Luminous efficacy	130 lm/W	ULOR	45%
		Total power	20 W

Light output 3 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	20 W	CRI	82
Total flux	2601 lm	LOR	100%
Luminous efficacy	130 lm/W	ULOR	45%
		Total power	20 W

Light output 4 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	20 W	CRI	82
Total flux	2601 lm	LOR	100%
Luminous efficacy	130 lm/W	ULOR	45%
		Total power	20 W

Light output 5 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	20 W	CRI	82
Total flux	2601 lm	LOR	100%
Luminous efficacy	130 lm/W	ULOR	45%
		Total power	20 W

Light output 6 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	20 W	CRI	82
Total flux	2601 lm	LOR	100%
Luminous efficacy	130 lm/W	ULOR	45%
		Total power	20 W

Light output 7 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	20 W	CRI	82
Total flux	2601 lm	LOR	100%
Luminous efficacy	130 lm/W	ULOR	45%
		Total power	20 W

Light output 8 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	20 W	CRI	82
Total flux	2601 lm	LOR	100%
Luminous efficacy	130 lm/W	ULOR	45%
		Total power	20 W

Light output 9 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	20 W	CRI	82
Total flux	2601 lm	LOR	100%
Luminous efficacy	130 lm/W	ULOR	45%
		Total power	20 W

Light output 10 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	20 W	CRI	82
Total flux	2601 lm	LOR	100%
Luminous efficacy	130 lm/W	ULOR	45%
		Total power	20 W

Mounting mode

Pendant

Shape and measurements

Length: 36.50 in

Width: 1.50 in

Height: 2.17 in

Electric

System power: 200 W

Protection

Adjustability

Height adjustable