


# Product data sheet

TANTO 1100 WHITE SENSOR 430LM 3000K RA>80 ON/OFF  
7021986415414  
SG ARMATUREN



Design: Hallvard Jakobsen Attractive, round wall luminaire with half-diffuser and cross that can be installed both indoors and outdoors. Made of die-cast powder-coated aluminium. Diffuser made of UV-stabilised opal polycarbonate. Two inputs/outputs for cables, option of both visible and concealed cabling, and loopable quick clips. Several variants with integrated sensor or dimming relay. Corrosion-proof with 10-year warranty, IP65 and vandal-resistant rating IK10. Light distribution Direct Light technic LED 11,5W 3000K Ra>80 SDCM 3 L70/B50 >50,000 hrs at Ta=25°C Control/Dimming On/Off Protection Class II IP65 IK10 Fire protection class: 850°C - 30s Energy and approvals A+ CE Materials and finish Housing: Aluminium Colour: White (RAL 9003) Optics: UV-stabilized polycarbonate Mounting/Connection Surface, Indoor / Outdoor Screwless terminal block Max. luminaires per circuit breaker: B10: 33, B16: 52, C10: 40, C16: 64

## Light output 1



1 x LED			
Nominal lamp power	11.5 W	LOR	100%
Lamp flux	430 lm	ULOR	9%
Luminous efficacy	37 lm/W	Total flux	430 lm
CCT	3000 K	Total power	11.5 W
CRI	80		

## Mounting mode

Wall mounted

## Shape and measurements

Length: 10.63 in  
Width: 4.84 in  
Height: 10.63 in

## Adjustability

Fixed

## Design

Color of housing: White

## Electric

System power: 11.5 W  
Appliance Class: II

## Protection

IP: 65  
IK: 10